


DALI  
Dimmable

Dimmable

Dimmable  
0/1...10

JLEDS is an official Distributor for these QLT LED Dimmable drivers , PBX-D types.

| Part Number  | Output<br>V | Output@230V<br>I max | W<br>@230V | Output@110V<br>I max | W<br>@110V | Dimensions<br>A x B x C | Protocol                |  |
|--------------|-------------|----------------------|------------|----------------------|------------|-------------------------|-------------------------|-------------------------------------------------------------------------------------|
| A40PB0X075DB | 12V/DC      | 6,25A                | 75W        | 5A                   | 60W        | 210 x 75 x 35           | DALI / 0-10V/1-10V/PUSH |                                                                                     |
| A40PBX7524DB | 24V/DC      | 3,12A                | 75W        | 2,5A                 | 60W        | 210 x 75 x 35           | DALI / 0-10V/1-10V/PUSH |                                                                                     |
| A40PBX100D0B | 24V/DC      | 4,16A                | 100W       | 2,5A                 | 60W        | 210 x 75 x 35           | DALI / 0-10V/1-10V/PUSH | •                                                                                   |
| A40PBX150D0B | 24V/DC      | 6,25A                | 150W       | 2,5A                 | 60W        | 210 x 75 x 35           | DALI / 0-10V/1-10V/PUSH | •                                                                                   |
| A40PBX200D0B | 24V/DC      | 8,33A                | 200W       | 3,75A                | 90W        | 210 x 75 x 35           | DALI / 0-10V/1-10V/PUSH |                                                                                     |



Datasheet download

### Alimentatore LED dimmerabile DALI/0-10V/ 1-10V/Push

- Alimentatore indipendente - IP20 - Classe II di isolamento
  - Comando DALI o pulsante (sul secondario, con memoria), 0-10V, 1-10V o potenziometro, selezionabile tramite impostazione dei dip-switches.
  - Possibilità di sincronizzare più alimentatori
  - Uscita in tensione costante 12/24V PWM
  - Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
  - Morsetti rapidi
  - Doppio morsetto d'uscita
  - Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
  - Alimentazione: 110÷240V/AC - Uscita stabilizzata.
- A richiesta, alimentazione a 230VDC o specifica potenziata a 110V

### Dimmable LED Driver DALI/0-10V/1-10V/Push

- For independent use - IP20 - Insulation class II
  - Dimming control by DALI or PUSH (on the secondary, with memory), 0-10V, 1-10V or potentiometer, selecting the dipswitch combination on board.
  - Possible synchronization of more drivers
  - Output in constant voltage 12/24V PWM
  - Self-resetting protection against overtemperatures, open circuit and against output short circuits
  - Fast terminals
  - Double output.
  - Cable clamp for flat and round cables
  - Input voltage: 110÷240V/AC - Steady output.
- On request, 230VDC input voltage or specific boosted 110V version

