


DALI
Dimmable

Dimmable

Dimmable
0/1...10

JLEDS is an official Distributor for these QLT LED Dimmable drivers , PBX-D types.

Part Number	Output V	Output@230V I max	W @230V	Output@110V I max	W @110V	Dimensions A x B x C	Protocol	
A40PB0X075DB	12V/DC	6,25A	75W	5A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	
A40PBX7524DB	24V/DC	3,12A	75W	2,5A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	
A40PBX100D0B	24V/DC	4,16A	100W	2,5A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	•
A40PBX150D0B	24V/DC	6,25A	150W	2,5A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	•
A40PBX200D0B	24V/DC	8,33A	200W	3,75A	90W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	



Datasheet download

Alimentatore LED dimmerabile DALI/0-10V/ 1-10V/Push

- Alimentatore indipendente - IP20 - Classe II di isolamento
 - Comando DALI o pulsante (sul secondario, con memoria), 0-10V, 1-10V o potenziometro, selezionabile tramite impostazione dei dip-switches.
 - Possibilità di sincronizzare più alimentatori
 - Uscita in tensione costante 12/24V PWM
 - Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
 - Morsetti rapidi
 - Doppio morsetto d'uscita
 - Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
 - Alimentazione: 110÷240V/AC - Uscita stabilizzata.
- A richiesta, alimentazione a 230VDC o specifica potenziata a 110V

Dimmable LED Driver DALI/0-10V/1-10V/Push

- For independent use - IP20 - Insulation class II
- Dimming control by DALI or PUSH (on the secondary, with memory), 0-10V, 1-10V or potentiometer, selecting the dipswitch combination on board.
- Possible synchronization of more drivers
- Output in constant voltage 12/24V PWM
- Self-resetting protection against overtemperatures, open circuit and against output short circuits
- Fast terminals
- Double output.
- Cable clamp for flat and round cables
- Input voltage: 110÷240V/AC - Steady output.
- On request, 230VDC input voltage or specific boosted 110V version