

1
Watt



IP 66


CRI>80




EMC



ta -20°÷ +40°C



IP66
350mA



JLEDS is an official Distributor for these High Brightness QLT Modules IP66: Floor in 2700K, 3000K, 4000K, 5000K, Blue, Red, Green and Amber.

High Brightness LED spot - 350mA - 1W

- Light power 119÷150 lumen
- Pressure assembly into a Ø 10mm hole
- Supplied standard with 1m FROR cable or with 5 m FEP cable (subcode 242)
- Available in standard colours 2700K, 3000K, 4000K and 5000K, plus Blue, Red, Green and Amber.
- Steppable (max 90 Kg.)

Spot a LED di potenza - 350mA

- Resa luminosa 119÷150 lumen
- Si monta a pressione in un foro da Ø 10mm
- Fornito standard con cavo FROR da 1m. Variante con cavo FEP da 5m (variante 242)
- Disponibile nei colori standard 2700K, 3000K, 4000K e 5000K
- Calpestabile (max 90 Kg.)

High Brightness LED-Spot - 350mA

- Lichtsleistung 119÷150 Lumens
- Druckeinsatz in einem Ø 10mm Loch
- Standard Mit 1m FROR Kabel oder 5m FEP Kabel (subcode 242)
- Verfügbar in Standardfarben 2700K, 3000K, 4000K und 5000K
- Max. Gewicht erlaubt: 90kg

Spot à LED de puissance - 350mA

- Rendement lumineux 119÷150 lumens
- Montage à pression dans un orifizio de Ø 10mm
- Livré équipé d'un câble FROR 1m ou d'un câble FEP de 5 m (subcode 242)
- Disponible en couleurs standard 2700K, 3000K, 4000K et 5000K
- Piétinable (max 90 Kg.)

Foco a LED de potencia - 1W - 350mA

- Capacidad luminosa 93÷111 lúmenes
- Montaja a presión en un orificio de Ø 10mm
- Suministrado con cable FROR de 1m o bien con cable FEP de 5 m (subcode 242)
- Disponible en colores estandar 2700K, 3000K, 4000K y 5000K
- Pisable (max 90 Kg.)

Part number	K	Lumen Typ.	Beam	Lux at 1 m	I (typ.)	V (typ.)	W (typ.)
A40FLOOR2700	2700K	119	Diffused	38	350 mA	2,9V	1W
A40FLOOR3000	3000K	123	Diffused	40	350 mA	2,9V	1W
A40FLOOR4000	4000K	130	Diffused	42	350 mA	2,9V	1W
A40FLOOR5000	5000K	150	Diffused	46	350 mA	2,9V	1W
A40FLOOR000C	BLUE	20	Diffused	n.d.	350 mA	3,1V	1W
A40FLOOR000R	RED	40	Diffused	n.d.	350 mA	2,9V	1W
A40FLOOR000V	GREEN	90	Diffused	n.d.	350 mA	3,1V	1W
A40FLOOR000A	AMBER	50	Diffused	n.d.	350 mA	2,9V	1W