

0,72
Watt


CV

IP 66

CRI>80

CE

EMC

M

M

F

ta -20°÷ +40°C

III


10 mm



ENERGY LABEL

ENERGIA

класс энергопотребления

A++

A+

A


B

C

D

E

IP66
12VDC



JLEDS is an official Distributor for these High Brightness QLT Modules IP66: PIN 3000K & 4000K.

 High Brightness LED spot - 12VDC

- Light power 66÷72 lumen
- Pressure assembly into a Ø 10mm hole
- Supplied standard with 1m FROR cable or with 5 m FEP cable (subcode 242)
- Available in 3000K and 4000K
- Steppable (max 90 Kg.)

 Spot a LED di potenza - 12VDC

- Resa luminosa 66÷72 lumen
- Si monta a pressione in un foro da Ø 10mm
- Fornito standard con cavo FROR da 1m. Variante con cavo FEP da 5m (variante 242)
- Disponibile nelle temperature di colore 3000K e 4000K
- Calpestable (max 90 Kg.)

 High Brightness LED-Spot - 12VDC

- Lichtsleistung 66÷72 Lumens
- Druckeinsatz in einem Ø 10mm Loch
- Standard Mit 1m FROR Kabel oder 5m FEP Kabel (subcode 242)
- Verfügbar in 3000K und 4000K
- Max. Gewicht erlaubt: 90kg

 Spot à LED de puissance - 12VDC

- Rendement lumineux 66÷72 lumens
- Montage à pression dans un trou de Ø 10mm
- Livré équipé d'un câble FROR 1m ou d'un câble FEP de 5 m (subcode 242)
- Disponible en couleurs 3000K et 4000K
- Piétinable (max 90 Kg.)

 Foco a LED de potencia - 12VDC

- Capacidad luminosa 66÷72 lúmenes
- Montaja a presión en un orificio de Ø 10mm
- Suministrado con cable FROR de 1m o bien con cable FEP de 5 m (subcode 242)
- Disponible en colores 3000K y 4000K
- Pisable (max 90 Kg.)

Part number	K	Lumen Typ.	Beam	Lux at 1 m	I (typ.)	V (max.)	W (typ.)
A40PIN123000	3000K	66	120°	14	60 mA	12V +/-5%	0,72 W
A40PIN124000	4000K	72	120°	16	60 mA	12V +/-5%	0,72 W