



JLEDS is an official Distributor for these Linear Fixed Strips. QLT Ref: MOD28 and MOD56.

Linear LED modules in constant current

- ZHAGA compatible constant current led modules
- High efficiency LED 2835
- Available in colors 3000K and 4000K, 3 steps Mac Adam
- Self dissipating
- Fast connection terminals
- Compatible with standard LEDIL and KHATOD optics

Moduli Lineari a LED a corrente costante

- Schede Led compatibili ZHAGA a corrente costante
- Led 2835 alta efficienza
- Disponibile nei colori 3000K e 4000K, 3 step Mac Adam
- Autodissipante
- Morsetti rapidi di collegamento
- Compatibile con ottiche standard Ledil e Khatod

High Brightness Linear LED-Module auf Kon-stantstrom

- Kompatibel mit ZHAGA Led-Modulen auf Konstantstrom
- High efficiency Led 2835
- In 3000K und 4000K Farbetemperaturen verfügbar. 3 steps Mac Adam
- Selbst verkühlbar
- Mit Schnellklemmenanschlüsse
- Kompatibel mit LEDIL und KHATOD Linsen.

Modules lineares à LED haute efficacité

- Modules à LED courant constant compatibles ZHAGA
- LED 2835 haute efficacité
- Disponibles en couleur 3000K et 4000K, 3 steps Mac Adam
- Autodissipant
- Connexions rapides
- Compatible avec optiques standard LEDIL et KHATOD

Mòdulos LED de alta eficiencia

- Módulos led de corriente constante compatibles con ZHAGA
- LED de alta eficiencia 2835.
- Disponibles en colores 3000K y 4000K, 3 steps Mac Adam
- Auto disipantes
- Terminales de conexión rápida
- Compatible con la óptica estándar LEDIL y KHATOD

Part number	K	Lumen Typ.	Led No.	V (typ.)	I (max)	W (typ.)	Dimensions A x B x H
A40MOD281630	3000K	960	16	12V	525mA	6W	280 x 20 x 6
A40MOD281640	4000K	960	16	12V	525mA	6W	280 x 20 x 6
A40MOD283230	3000K	1200	32	12V	1050mA	12W	280 x 20 x 6
A40MOD283240	4000K	1200	32	12V	1050mA	12W	280 x 20 x 6
A40MOD563230	3000K	1920	32	24V	525mA	12W	560 x 20 x 6
A40MOD563240	4000K	1920	32	24V	525mA	12W	560 x 20 x 6
A40MOD566430	3000K	3840	64	24V	1050mA	24W	560 x 20 x 6
A40MOD566440	4000K	3840	64	24V	1050mA	24W	560 x 20 x 6