



MINI SPOT LED Downlight




MINI SPOT 25
1W & 2W




MINI SPOT 30
1W, 2W & 3W




MINI SPOT 35
1W, 2W & 3W



MINI SPOT 40
1W, 2W & 3W



MINI SPOT 45
1W, 2W, 3W, 4W & 5W



» **Cree** LEDs IP20 | UGR < 19 | ROHS |

Feature

- Small and compact recessed down light for accent lighting, and very easy to install.
- Full cover Halogen lamp application.
- Smaller aperture for low glare architect application.
- Support for all common dimming systems (Triac, DALI, 1-10V).
- Impressive 50,000 hours system lifetime, 3 years warranty

STANDARD MODEL



Product Code	Lumen output	Beam	System power	Efficiency	LED
MSPOT-20-1W	90 lm	12/25/30/40°	1 W	90 lm/W	CREE
MSPOT-20-2W	150 lm	12/25/30/40°	2 W	75 lm/W	CREE

STANDARD MODEL



Product Code	Lumen output	Beam	System power	Efficiency	LED
MSPOT-30-1W	90 lm	20/30/45/60°	1 W	90 lm/W	CREE
MSPOT-30-2W	150 lm	20/30/45/60°	2 W	75 lm/W	CREE
MSPOT-30-3W	200 lm	20/30/45/60°	3 W	66 lm/W	CREE

STANDARD MODEL



Product Code	Lumen output	Beam	System power	Efficiency	LED
MSPOT-35-1W	100 lm	20/30/40°	1 W	100 lm/W	CREE
MSPOT-35-2W	160 lm	20/30/40°	2 W	80 lm/W	CREE
MSPOT-35-3W	220 lm	20/30/40°	3 W	73 lm/W	CREE

STANDARD MODEL



Product Code	Lumen output	Beam	System power	Efficiency	LED
MSPOT-40-1W	100 lm	10/20/40/60°	1 W	100 lm/W	CREE
MSPOT-40-2W	200 lm	10/20/40/60°	2 W	100 lm/W	CREE
MSPOT-40-3W	260 lm	10/20/40/60°	3 W	86 lm/W	CREE

STANDARD MODEL



Product Code	Lumen output	Beam	System power	Efficiency	LED
MSPOT-45-1W	90 lm	10/20/40/60°	1 W	90 lm/W	CREE
MSPOT-45-2W	180 lm	10/20/40/60°	2 W	90 lm/W	CREE
MSPOT-45-3W	250 lm	10/20/40/60°	3 W	83 lm/W	CREE
MSPOT-45-4W	380 lm	15/24/36/60°	4 W	95 lm/W	CREE / CITIZEN
MSPOT-45-5W	480 lm	15/24/36/60°	5 W	96 lm/W	CREE / CITIZEN