



CE EMC IP20 RoHS

Type	Part N°	Dimensions (mm)	Colour	Lumen (lm)	Input V	Beam °	Power Max (W)	Installation hole (mm)	Packing box dimensions (mm)	Weight (kg)
TUNE CCT 6W	BDPL0806CCTB	Ø 115x32h	3000 - 4200 - 6000K	480	175÷240	120°	6	Ø 105	119x119x47h	0,12
TUNE CCT 12W	BDPL0812CCTB	Ø 170x32h	3000 - 4200 - 6000K	960	175÷240	120°	12	Ø 155	174x174x47h	0,21
TUNE CCT 20W	BDPL0820CCTB	Ø 240x32h	3000 - 4200 - 6000K	1600	175÷240	120°	20	Ø 225	244x244x47h	0,40

-  **Incasso a LED tondo ad alta potenza 230V CCT**
- Selettore per scelta colore (3000K - 4200K - 6000K)
 - Installazione semplice e veloce
 - Funziona direttamente a tensione di rete con alimentatore incorporato
 - Lunga durata

-  **Round extra powerful 230V recessed CCT LED downlight**
- Switch for color setting (3000K - 4200K - 6000K)
 - Easy and quick installation
 - Works directly with mains voltage (Built-in driver)
 - Long life time

-  **CCT LED Rundenbastrahler 230V**
- Switch für Farbauswahl (3000K - 4200K - 6000K)
 - Einfache und schnelle Installation
 - Betrieb direkt auf 230V mit ein gebautem Led-Treiber
 - Lange Lebensdauer

-  **Encastrement LED rond CCT haute puissance 230V**
- Programmeur de teintes (3000K - 4200K - 6000K)
 - Installation simple et rapid
 - Alimentation intégrée, branchement direct sur le réseau
 - Longue durée de vie

-  **Focos empotrables a LED de alta potencia 230V CCT**
- Selector de colores (3000K - 4200K - 6000K)
 - Instalación rápida y fácil
 - Alimentación directa 230V (convertidor integrado)
 - Larga duración

Connettere direttamente a 175÷240V
Connect direct to 175÷240V

**CONNECT
230V
DIRECT**

Driver incorporato
Built-in driver



- 3000K
- 4200K
- 6000K

